


Teknik Veri Tablosu

	Hazne Kapasite	Soğutma Aralığı °C
C1/P1	19L	+3....+6
C2/P2	19+19L (48L)	+3....+6
C3/P3	19+19+19L (57L)	+3....+6
C4/P4	19+19+19+19L (76L)	+3....+6




Koliiz Boyut/kg	X	Y	Z	kg
C1/P1	265mm	670mm	585mm	26
C2/P2	480mm	670mm	585mm	44.5
C3/P3	695mm	670mm	585mm	59
C4/P4	905mm	670mm	585mm	74.7

Kolili Boyut/kg	X	Y	Z	kg
C1/P1	270mm	740mm	590mm	29.5
C2/P2	485mm	740mm	590mm	49
C3/P3	705mm	740mm	590mm	66.5
C4/P4	920mm	740mm	590mm	83.5

Teknik Tablo R134a	Soğutma Kapasitesi	Güç	Akım	Besleme Voltajı
C1/P1	389W	211W	1.78A	220-240V / 50-60Hz
C2/P2	705W	301W	1.93A	220-240V / 50-60Hz
C3/P3	838W	372W	2.58A	220-240V / 50-60Hz
C4/P4	1133W	524W	3.06A	220-240V / 50-60Hz

Technical Data Table

	Tank Capacity	Cooling Range °C
C1/P1	19L	+3....+6
C2/P2	19+19L (48L)	+3....+6
C3/P3	19+19+19L (57L)	+3....+6
C4/P4	19+19+19+19L (76L)	+3....+6



Dimension/kg	X	Y	Z	kg
C1/P1	265mm	670mm	585mm	26
C2/P2	480mm	670mm	585mm	44.5
C3/P3	695mm	670mm	585mm	59
C4/P4	905mm	670mm	585mm	74.7

Boxed Dimension/kg	X	Y	Z	kg
C1/P1	270mm	740mm	590mm	29.5
C2/P2	485mm	740mm	590mm	49
C3/P3	705mm	740mm	590mm	66.5
C4/P4	920mm	740mm	590mm	83.5

Technical Table R134a	Cooling Capacity	Power	Current	Voltage
C1/P1	389W	211W	1.78A	220-240V / 50-60Hz
C2/P2	705W	301W	1.93A	220-240V / 50-60Hz
C3/P3	838W	372W	2.58A	220-240V / 50-60Hz
C4/P4	1133W	524W	3.06A	220-240V / 50-60Hz